Support for Remote Access to On-Line Subsets of EOSDIS HDF Datasets

Elaine Dobinson, P.I. Todd Karakashian, Tech. Rep.

Jet Propulsion Laboratory

Elaine.Dobinson@jpl.nasa.gov Todd.K.Karakashian@jpl.nasa.gov

Objectives

- Efficient access to remote on-line HDF datasets
 - » Allow remote subsetting, sampling, browsing of HDF files without transferring large volumes of data over the network.
- Support for existing HDF science applications and information infrastructure
 - By relinking with DODS versions of HDF libraries, existing HDF applications become network clients which can access remote data in multiple standard formats stored on World Wide Web servers.
- Interoperability between multiple standard data format
 - » JPL prototype will add HDF support to DODS.
 - With the JPL contribution, DODS will provide automatic translation between HDF, netCDF and JGOFS formats

What is DODS?

- DODS is a Distributed Oceans Data System in which --
 - Existing or new science analysis programs are transformed into network clients which can access datasets remotely
 - » DODS provides replacement versions of HDF, netCDF or JGOFS libraries with which applications can be relinked.
 - » The replacement libraries handle network access and data format translation automatically. Remote files appear as if they were local and in the format the application understands.
 - » With DODS the domain of the typical science application is expanded from the local computer file system to the set of science WWW servers on the Internet.
 - » Scientists have direct control over data access via their applications; no unwieldy and restrictive "retrieval system" is interposed between the data and the data analysis software.

What is DODS? (cont.)

- Science data are exported to the Internet via WWW (httpd) servers
 - » Data providers need only install a few DODS CGI programs at their Web site
- Data format interoperability is provided via the DODS Data Access Protocol (DAP)
 - » Client data requests are encoded into URL's and transmitted via HTTP to the WWW server.
 - Data returned are translated on the server side from the native format into the DAP and sent to the client; the client interprets the data encoded in the DAP and returns them in the form expected by the application.
 - » Because the DAP is used as the intermediate data format, translation between any of the DODS-supported data formats is possible.

EOSDIS Technology Transfer Workshop ______ November 14, 1995

JPL Approach

Develop DODS HDF Server software

- convert URL-encoded data and metadata requests into HDF API calls on data residing on server
- translate HDF API return values into DODS Access Protocol structures and send to client.

Develop DODS surrogate HDF API library

- » convert client application HDF API calls into URL-encoded requests for data from server.
- » translate DODS Access Protocol responses into return values from client application HDF calls.

Evaluate and demonstrate prototype using EOSDIS software and **AVHRR Oceans Pathfinder dataset**

- » relink EOSView application with DODS surrogate HDF libraries to permit remote browsing of AVHRR Oceans Pathfinder dataset.
- look at other potential EOSDIS client software for use with DODS

EOSDIS Technology Transfer Workshop —————————————————————————November 14, 1995

Architecture

application program

surrogate HDF library

Internet




network interface Client Component

(via DODS Data Access

Protocol over WWW)

Remote Server



EOSDIS Technology Transfer Workshop

_______ November 14, 1995

JPL TIMELINE

Preliminary Activities

10/01/95 - 11/10/95

setting up development H/W and S/W

learning about DODS, HDF, C++, WWW technology

***** time out for surgery, recuperation, holidays *****

HDF Server Development

01/02/96 - 04/30/96

design, code, test, doc

Client Libraries Development

05/01/96 - 08/31/96

design, code, test, doc

Documentation

09/01/96 - 09/15/96

DODS HDF Server Admin Guide

DODS Client Library Users' Guide

Testing and Preparation

09/16/96 - 12/31/96

testing with HDF data demonstrations to ESDIS and DODS